

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
5 February 2004 (05.02.2004)

PCT

(10) International Publication Number
WO 2004/011093 A1

(51) International Patent Classification⁷: A61N 2/02

(21) International Application Number:
PCT/GR2003/000031

(22) International Filing Date: 22 July 2003 (22.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
020100362 25 July 2002 (25.07.2002) GR

(71) Applicants and

(72) Inventors: ANNINO, Nicolai [GR/GR]; 4 Alexandrou Panagouli, GR-68100 Alexandroupolis (GR). TSAGAS, Ioannis [GR/GR]; Opisthen N.E. Katikies, GR-67100 Xanthi (GR).

(74) Common Representative: TSAGAS, Ioannis; Opisthen N.E. Katikies, GR-67100 Xanthi (GR).

(81) Designated States (*national*): AE, AT, AU, BG, BR, BY, CA, CN, CU, DE, DK, ES, FI, GB, HU, IL, IN, JP, MA, MG, MX, NO, NZ, PH, PL, RO, RU, SE, TR, UA, US, ZA.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ELECTRONIC DEVICE FOR STRENGTHENING THE IMMUNE SYSTEM



(57) Abstract: One electronic device proper for strengthening the immune system, produces magnetic fields with characteristics which are determined by a multi channel biomagnetometer. The electronic device is including an alternating current output generated by a microcontroller of symmetric square wave signals with a specific frequency which is regulated by one integrated circuit which receives the frequency value from a keyboard or from a computer through a serial port and an interface integrated circuit and supplies a great number of coils, up to 122, with hemispheric or plane arrangement for the production of symmetric square wave signal of magnetic fields. The electronic device is including also a liquid crystal display and a crystal of high constant oscillation for timing of the system. The strengthening of the immune system is accomplished with the decomposing removal of all placed complex inorganic substances from the glands of the brain with the help of the spiral oscillations of the plasma ions in the blood and this results to energize these glands for better hormone production and activation of the brain.

WO 2004/011093 A1

BEST AVAILABLE COPY

ELECTRONIC DEVICE FOR STRENGTHENING THE IMMUNE SYSTEM

5 BACKGROUND OF THE INVENTION

Field of the invention

10 The present invention relates to an electronic device for strengthening of the immune system with the use of magnetic fields the characteristics of which are determined by multi channel biomagnetometer. The electronic device employs a microcontroller for producing an alternating current of regulated specific frequency which supplies a great number of coils, about 122, in a specific hemispheric or plane arrangement, in order to cover the whole brain or other parts of the body, for the
15 production of alternating symmetrical magnetic fields of positive symmetrical square wave signal. The intensity and frequency of the alternating current is regulated with a specific binary system according to the frequency and intensity which are determined during the diagnosis with the 122 multi channel biomagnetometer. The strengthening of the immune system is accomplished with the removal of the calcium and other
20 similar chemical elements from the pineal gland and other brain glands. With this removal is accomplished better action and function of the glands for the production of inhibitory hormones, as is the melatonin, which are necessary for the removal of the free radicals which are produced during oxidation. The removal of the inorganic substances from the glands is accomplished with the help of the spiral oscillations of
25 the electrical charged plasma ions in the brain around and along the magnetic lines of the alternating magnetic field. In addition it can be accomplished better adjustment in the ion concentrations which are necessary for better neuronal function.

Prior Art

30 There is no relevant bibliography existing in prior art with respect to the strengthening of the immune system with the influence of magnetic fields.

SUMMARY OF THE INVENTION

35 The first object of the present invention is to provide an electronic device which helps the strengthening of the immune system with the influence of alternating magnetic fields of special form and specific frequency and intensity which are determined with the use of the multi channel biomagnetometer, microcontroller for
40 producing an alternating current of square wave signal and low frequency supplies through resistors a great number of coils, up to 122, which are in specific hemispheric or plane arrangement, in order to cover the whole brain or other parts of the body, for the production of alternating magnetic fields of positive symmetrical square wave signal with 50% duty cycle. These magnetic fields force the charged plasma ions,
45 according to the alpha rhythm frequency of each individual, in spiral oscillations around the magnetic lines of square form. The above ions decompose and remove the complex inorganic substances from the brain glands and this has as a result to activate and to energize these glands for better hormone production, as for example the melatonin which is produced by the pineal gland, which are useful for the immune

system and for the neurons. The decrease of melatonin concentration is related with many dysfunctions of the organism.

5 A second object of this invention is to provide an electronic device to produce very low magnetic fields as is the intensity, the wave signal and the frequency which are emitted from each person and they are determined with magnetoencephalographic measurements by the multi channel biomagnetometer, which is based on the superconductivity of some specific substances in very low temperatures. Every change in the magnetic field is measured by the biomagnetometer as a current which can be interpreted from it as a potential difference which can be amplified and measured properly.

10 The above mentioned objects of the present invention are implement with the use of an electronic device to produce magnetic fields with the characteristics of the magnetic fields which have measured from the brain with the multi channel biomagnetometer, are alternating of square wave signal with intensity of the order of some pT and of low frequency up to 15Hz. The device is able to produce similar magnetic fields from a large number of coils, up to 122, which are in hemispheric or plane arrangement so that to cover all 5 brain regions or other parts of the body. The positive symmetrical square wave signal has given the best results.

20

BRIEF DESCRIPTION OF THE DRAWINGS

The application of the invention is described below by reference to the accompanying drawings wherein the above mentioned objects and other novel features of this invention will become apparent to those skilled in the art.

25 FIG.1 shows a perspective view of five groups of 61 coils of spiral form wherein the groups of coils of the device in accordance with the present invention are in hemispheric or plane arrangement so that to cover the five brain regions of the skull or other parts of the body. All the coils are connected in parallel through resistors with an alternating current output and produce all the coils similar magnetic fields with similar characteristics. The number of coils can be increased up to 122.

30 FIG.2 shows a schematic diagram of the electronic circuit of the device where in accordance with the present invention comprises an alternating current output, one microcontroller, a liquid crystal display (LCD), a keyboard or a programmable integrated circuit, a serial port, an integrated circuit to interface the microcontroller to a computer, resistors, capacitors, multiposition rotary timing switch, potentiometers and a power source or a power supply battery of 6Volts.

40 DETAILED PRESCRIPTION OF PREFERRED EMBODIMENTS

The detailed description of the preferred embodiments and drawings herein after being made by reference to the accompanying drawings, does not intend to limit the scope of the invention, and it will be readily understood by one skilled in the art that the present invention is not anticipated by the prior art.

45 One way of application of the invention is described by reference to the included figures.

The electronic device consists of five groups of spiral form coils (1) printed on flexible plastic plates.

50 The group (2) consists of up to 52 coils. The groups (3) and (4) consist of up to 12 coils each one, the group (5) consists of up to 20 coils and the group (6) consists of

up to 24 coils. These groups cover completely the five different regions of the skull and are in hemispheric arrangement inside one helmet or plane arrangement on the surface of a flexible plastic plate. The end (21) of all coils (1) is connected in parallel through resistors with the alternating current output (9) and the other common end of all coils is grounded. All coils are supplied with the same current intensity and produce simultaneously alternating magnetic fields of positive square wave symmetrical signal with 50% duty cycle of the same intensity and frequency. The coils are made by a good conductive metal and are printed on flexible plates. The diameter of the coils (1) can be from 0.5cm up to 2.5cm. The device comprises also one microcontroller (10) as an integrated circuit which recognizes and works out the data given by the key board type matrix (8) or a programmable circuit (29) or other button, for programming alternating current with frequency and shape which are produced by microcontroller (10) according to the data given by the computer (27) for frequency programming using the appropriate program through the serial port (22) used for operation frequency programming and the interface integrated circuit (23) to the microcontroller (10), one Liquid Crystal Display (LCD) (7) for interface, the potentiometer (11) to regulate the contrast of the Liquid Crystal Display (LCD) and the potentiometer (12) to regulate the intensity of the alternating current which is a function of the intensity of the magnetic fields so that to have the same value with the intensity determined by the multi channel biomagnetometer for the examined individual. The operation time of the device is regulated by a multiposition or a rotary timing switch (24) through the microcontroller (10). The resistances (28) as a pull up resistor with common end with the electric source connect in parallel the programmable circuit (29) with the rotary timing switch (24) and the microcontroller (10).

The device comprises also pull-down resistors (13) to increase the potential, the resistors (14) and (15) and also capacitors (16) and (17) for crystal oscillator operation and the time operation crystal (18) for the timing frequencies of the system. The resistances are ranged from several tens of Ohm up to several tens of kOhm and the capacitance of the capacitors is ranged from several pFarad up to several nFarad. Finally the device comprises an electrical DC power supply or battery from +5V up to +12V (19) with two diodes in series to drop the total Voltage. The microcontroller (10) controls also the good function of the device by indicating LED (30) and of the power supply by indicating LED (31).

The microcontroller (10) is using the inside comparator to check the battery level and provided that the battery is in good condition a button is pressed to go to programming mode by which the frequency of the output signal can be changed. If the button is not pressed then the operation time can be defined by the rotary timing switch and a square wave signal at the output pin is produced by the microcontroller (10).

The ions perform spiral trajectories around the magnetic lines of the alternating magnetic field which is emitted from the coils (1), which are placed in such a way so that the orientation of some part of the magnetic lines to coincide with the flow of the blood plasma, so that the charged plasma ions in the brain to move in spiral form around those parts of the magnetic lines which are parallel to the flow of blood plasma. During the change in direction of the magnetic field the ions are forced to change direction of rotation. These abrupt changes, which are done usually with the alternating magnetic fields of square wave form, cause friction of the plasma ions with calcium and other inorganic substances which are placed on the pineal gland and

other brain centers, so that to break the connection binding of the calcium atoms and to remove those atoms from the brain glands.

5 The Biomagnetometer of superconductive quantum interference is based on Josephson effect of superconductivity which is the following: When two superconductive metals come in touch with one very thin foil of an insulator which is placed between them then electrons are passing through the insulator from one metal to another metal. The flow of electrons, which is known as Josephson current, is interrupted if a constant voltage is applied between the two metals and the electrons start to flow again with the application of an alternating voltage of high frequency.

10 When two superconductive metals with a horseshoe shape come in touch with two thin insulator foils then two Josephson currents appeared which are interfered between them. If in the neighborhood of these metals there is an alternating magnetic field then it is possible to measure the Josephson current as a function of the alternating magnetic field. On this principle is based the construction of the superconductive

15 quantum interference device with which it is possible to measure very small alternating magnetic fields of the order of few pTesla.

The biomagnetometer consists from one or more receiving antennas, one container for the liquid He(-269°C) and the necessary electronics. The signal is analysed by linear and nonlinear methods to come to the conclusions about the

20 operational functions of various organs of the body.

CLAIMS

1. The electronic device for strengthening the immune system with the use of magnetic fields based on the characteristics which are determined using the multi channel biomagnetometer said electronic device including a great number of coils (1) up to 122, said coils are arranged in groups (2), (3), (4), (5), (6), in hemispheric and plane arrangement, one alternating current output (9), one microcontroller (10), one keyboard (8), a programmable circuit (29) for programming alternating current with frequency and shape formed by said microcontroller (10) according to the data given by the computer (27) through a serial port (22) and an interface integrated circuit (23) to said microcontroller (10), a Liquid Crystal Display (LCD) (7), two potentiometers (11) and (12), a number of resistors (13),(14),(15), (28) and capacitors (16),(17),(20), a rotary timing switch (24) to regulate the operation time through said microcontroller (10), one electrical power supply (19) and indicating LEDs (30), (31).
2. The electronic device for strengthening of claim 1 wherein said coils (1) made by good conductive metal up to 122 are of spiral plane form arranged in said five groups (2), (3), (4), (5), (6) in a special hemispherical arrangement inside in specific helmet so that to cover completely the five specific regions of the skull or said coils (1) are arranged on a flexible plastic plate so that to cover other parts of the body, where the end (21) of all said coils (1) is connected in parallel through resistors with the alternating current output (9), wherein the other common end of all said coils (1) is connected with the ground.
3. The electronic device for strengthening of claim 1 wherein the produced magnetic fields are alternating of positive symmetrical mostly square wave signal with low frequencies from 1 up to 20 Hz which can be regulated up to the first decimal digit so that to force the blood plasma charged ions in the brain to rotate in spiral trajectories around the magnetic lines with alternating direction of rotation which breaks by causing friction and removes the foreign substances which are placed on the brain glands for better hormone production and strengthening of the immune system.
4. The electronic device for the strengthening of claim 1 is including one only alternating current output (9) of square wave signal of frequency from 1 up to 20Hz which supplies a great number of said coils (1) up to 122.
5. The electronic device for strengthening of claim 1 is including one said microcontroller (10) as an integrated circuit which recognizes and works out the data given by said keyboard (8) or programmable circuit (29) for programming alternating current with frequency and shape produced by said microcontroller (10), which regulates the magnetic fields characteristics and the regular function of the device.
6. The electronic device for strengthening of claim 1 is including said microcontroller (10) with the ability to accept data given by said computer (27) for frequency programming with appropriate program through said serial port (22) and said interface integrated circuit (23) to work out and produce alternating current and magnetic fields of desirable characteristics.
7. The electronic device for strengthening of claim 1 is including for interface a Liquid Crystal Display (LCD) (7) for optical indication of the characteristics parameters of the magnetic fields, pull-down resistors (13) to increase the potential, the resistors (14) and (15) and also capacitors (16), (17) and (20) for crystal oscillator operation and the time operation crystal of high frequencies oscillation (18) for the timing frequencies of the system, a potentiometer (12) to regulate the intensity of the alternating current, a rotary timing switch (24) to regulate the operation time and a

power supply or battery (19) with two diodes in series to drop the total Voltage and indicating LED (31) for changing the batteries.

- 5 8. The electronic device for strengthening of claim 1 is including a serial port (22) for operation frequency programming, an interface integrated circuit (23) to connect said computer (27) with said microcontroller (10) which controls also the good function of the device by an indicating LED (30), a rotary timing switch (24) and the resistances (28) as pull up resistor with a common end connected to the electric source and also connecting in parallel said programmable circuit (29) with said rotary timing switch (24) and said microcontroller (10) and said potentiometer (12).
- 10




Fig-1

Fig-2